

Frequently Asked Questions

Steintec Utility Mortars FAQ

Which products are part of the 'Utility' range?

Products that are included under in the 'Utility' range include; tuffbed, tuffbond Utility, tufftop Utility, tuffjoint Utility and tufffix.

How do I mix your Utility mortars?

Method statements for all our products can be found on our website www.steintec.co.uk/mortar-methodstatements. tuffjoint Utility is applied without any mixing.



What temperatures can your mortars be used at?

Our mortars can be used between 2°C and 30°C. DO NOT lay bedding or joint paving if the temperature is below 3°C on a falling thermometer, or below 2°C on a rising thermometer.

Will temperatures affect curing times?

Yes, at lower temperatures mortars take longer to cure, final performance generally is unaffected above 2°C.

Can I use the products when raining?

Our products can be used in light rain. Excess tuffjoint Utility can not be returned to the tub for future use if wet.

Can your mortars be used on step treads, risers & edgings?

Yes, both tufftop Utility and tuffjoint Utility can be used on step treads, risers and edgings. A PDF guide for how to do this on our website. www.steintec.co.uk/_img/pics/pdf_1673539933.pdf



How long until I can drive or park on tufftop Utility or tuffjoint Utility on a driveway?

Based on an ambient 20°C temperature we would recommend 7 days for full strength but could be used after a minimum of 24 hours.

What is the m² coverage per bag or tub of your products?

Our online calculator at www.steintec.co.uk/utility-calculator will give you results based on your project size and materials being used.

The m² coverage of all our products vary depending on thickness of the bedding & the size of the paving units.



tuffbed	Bedding Depth	kg per m ²	m ² per 25 kg
	25 mm	55 kg/m ²	0.45 m ²
	40 mm	88 kg/m ²	0.28 m ²
	50 mm	110 kg/m ²	0.23 m ²

tuffbond Utility	~1.5 kg/m ² per layer
	~16 m ² per 12 kg tub (1 mm coat)
	~8 m ² per 12 kg tub (2 mm coat)

tuffjoint Utility	Paving Unit Size	Joint Width	m ² per 12.5 kg
	600 x 1200 x 20 mm	4 mm	31 m ²
	600 x 600 x 20 mm	5 mm	19 m ²
	600 x 900 x 20 mm	6 mm	19 m ²
	600 x 900 x 24 mm	8 mm	11 m ²
	600 x 600 x 24 mm	10 mm	8 m ²

tufftop Utility	Paving Unit Size	Joint Width	m ² per 12 kg
	600 x 1200 x 20 mm	4 mm	27 m ²
	600 x 600 x 20 mm	4 mm	20 m ²
	600 x 900 x 20 mm	6 mm	19 m ²
	600 x 900 x 24 mm	8 mm	10 m ²
	600 x 600 x 24 mm	10 mm	7 m ²

Steintec[®]
high performance paving mortars

1 Northwick Road, Canvey Island, Essex, SS8 0PU

+44 (0) 203 598 9800

www.steintec.co.uk

Frequently Asked Questions

Pavement Care FAQ

What products can I use to protect my paving?

Weiss Stain Protect Pro; provides protection against stubborn pavement grime.

Weiss Colour Enhancer; gives your paving a wet look enhancement as well as protection.

Weiss Install Protect; is a pre-construction protection for all paving types. It helps to protect against contaminants often associated with construction sites.

How can I remove any cement stains from my paving?

Weiss Cement Stain Remover (CSR); suitable for most types of granite, acid-resistant natural stone, man-made paving and flooring elements such as ceramic tiles and terracotta.

I have rust stains on my drive?

Weiss Rust Remover; removes rust stains from a variety of natural stone including granite and some sandstone.

Do you have any products to remove oil and fat stains?

Yes, Weiss Oil & Grease Stain Remover removes deep and stubborn oil and fat stains from all types of pavement surfaces.

My paving is looking green due to algae and weeds, what is the best way to clean this?

Weiss Organic Stain Remover; is a powerful alkaline surface cleaner that removes, kills and helps prevent growth of moss, weeds etc.

Weiss Algae & Moss Treatment; removes and helps prevent algae and moss stains within hours of application. Continues to work for weeks after to prevent further regrowth.

Is there something that I can use to clean my paving without damaging it?

Weiss Professional Paving Cleaner; is a pH neutral and solvent free cleaner that can be used for general or intensive spot cleaning on all types of natural stone and concrete pavements.



Steintec[®]
high performance paving mortars

1 Northwick Road, Canvey Island, Essex SS8 0PU

+44 (0) 203 598 9800

www.steintec.co.uk